



**greenlux**  
cost reduction LED lighting

## Glamour D Surface Mounted LED Downlight



### Specifications

<b>Colour Range</b>	2700-4000k
<b>Chipset</b>	COB
<b>Power Consumption</b>	10W
<b>Lumen</b>	1000lm
<b>Input Voltage</b>	100 ~ 240V AC
<b>Beam angle</b>	24° / 36° / 60°
<b>CRI</b>	>80 or 90
<b>Power Factor</b>	>0.9
<b>IP Rating</b>	IP20

- UGR<19
- Exquisite design with strict product quality control
- Low light decay
- High lumen output up to 100lm/W
- High quality Sharp or Cree COB LED chipset
- Reliable TUV constant current isolated driver
- Superior pure aluminum housing with high quality coating for finishing color
- IP20 Rated
- Applications include offices, shopping centres, hotels, restaurants, museums, public areas & households

### Dimensions & Material

<b>Product Dimension (mm)</b>	10W	Ø57 * 600
<b>Housing Material</b>	Aluminium Housing	
<b>Housing Color</b>	Black / White / Silver	
<b>Warranty</b>	5 Years	






**greenlux**  
cost reduction LED lighting

## GVGLA-10W-C

**COB LED CRI≥80 IP20**


Powder-coated: White Silver Black  
Color temperature: 2700K 3000K 4000K  
Beam angle: 24° 36° 60°



## GVGLA-6W-A

**COB LED CRI≥80 IP20**

Powder-coated: White Silver Black  
Color temperature: 2700K 3000K 4000K  
Beam angle: 24° 36° 60°



## GVGLA-10W-D



**COB LED CRI≥80 IP20**

Powder-coated: White Silver Black  
Color temperature: 2700K 3000K 4000K  
Beam angle: 24° 36° 60°

## GVGLA-6W-B

**COB LED CRI≥80 IP20**

Powder-coated: White Silver Black  
Color temperature: 2700K 3000K 4000K  
Beam angle: 24° 36° 60°





**greenlux**  
cost reduction LED lighting

## Glamour D Surface Mounted LED Downlight

Model

Model#	Dimensions (mm)	IP Rating	Beam Angle	CCT	Lumens	Wattage	LED	Dimmer (option)
GVGLA-6W-A	Ø57 * 300	IP20			600	6W	COB	Triac
GVGLA-6W-B	Ø57 * 300	IP20	24°	2700-4000k	600	6W	COB	Triac
GVGLA-10W-C	Ø57 * 600	IP20	30°		1000	10W	COB	Triac
GVGLA-10W-D	Ø57 * 600	IP20	60°		1000	10W	COB	Triac

