



greenlux
cost reduction LED lighting



Comet Series **Cylinder** Outdoor LED Wall Light

Available in Multiple Wattage
80% lumen maintenance at 50,000 hours

- No UV or IR rays. No mercury
- Replaces traditional Outdoor Wall Lights
- Triac dimmer system for option
- High lumen output
- High quality COB & SMD chipset
- High quality Die-casting Aluminium housing
- IP54 & IP65 Rated (sheltered & waterproof)
- 3 Years Warranty
- Applications include sheltered & outdoor areas such as corridors, walkways for hotels, clubs, museums, exhibition centres & household

Specifications

Colour Range	3000-6000k
Luminous Flux	300lm ~ 2000lm
Power Consumption	Down 3W Up/Down 2*3W Up/Down 2*10W
Input Voltage	100 ~ 240V AC 60Hz
LED Current	350 ~ 700mA
Operating Temp.	-20°C to 50°C
Beam angle	30° ~ 55°
Ra	>82
Chipset	COB & SMD
IP Rating	IP54 & IP65
Dimmable	Triac Dimmer (option)



Dimensions & Materials

Product Dimensions (mm)	Down	60*110*125
	Down	80*86*80
	Down	80*90*136
	Up/Down	60*110*180
	Up/Down	60*130*180
	Up/Down	90*130*180

Housing Material	Powder Coated Aluminium + Clear Diffuser
Housing Colour	Black / Silver

Certification and Safety

Certifications	CE, RoHS, SAA, RCM
Environment	Sheltered & Outdoor Location
Warranty	3 years






greenlux
cost reduction LED lighting


Comet Series **Cylinder** Outdoor LED Wall Light

Dimensions


Down




Down



Down




Up/Down



Up/Down



Up/Down



Model

Model#	Dimensions (mm)	IP Rating	Beam Angle	CCT	Lumens	Wattage	LED	Dimmer (option)
GJCOM-3W	60*110*125	IP54	30°/55°	3000-6000k	300	3W	SMD	Triac
GJCOM-3W	80*86*80	IP54	30°/55°	3000-6000k	300	3W	SMD	Triac
GJCOM-3W	80*90*136	IP54	30°/55°	3000-6000k	300	3W	SMD	Triac
GJCOM-6W	60*110*180	IP54	30°/55°	3000-6000k	600	2*3W	SMD	Triac
GJCOM-6W	60*130*180	IP54	30°/55°	3000-6000k	600	2*3W	SMD	Triac
GJCOM-20W	90*130*180	IP65	30°/55°	3000-6000k	2000	2*10W	COB	Triac