


LED Surface Mounted Down Light



Specification

Product code:	GUROL-15W-L
Power:	15W
Electric data:	AC 220-240V 50/60Hz
Lumen:	1300 - 1750lm
Beam angle:	36° / 60°
Color temperature:	3000K / 4000K / 5000K
IP class:	IP20
CRI:	>80 / >90
Current:	350mA
LED source:	COB LED
Fixture material:	Aluminum
Finish:	White / Black



Measurement

Model	Dimension(mm)			Size(mm)
	A	B	C	
15W	85	186	57	Ø85*186

LM80

3 Yrs
Warranty

RCM

SAA

IP20

TUV

9/331 Ingles Street
Port Melbourne VIC 3207 Australia

info@greenlux.com.au
sales@greenlux.com.au


T 1300 650 625
www.greenlux.com.au

LED Surface Mounted Down Light



Specification

Product code:	GUROL-25W-L
Power:	25W
Electric data:	AC 220-240V 50/60Hz
Lumen:	2150 - 2900lm
Beam angle:	36° / 60°
Color temperature:	3000K / 4000K / 5000K
IP class:	IP20
CRI:	>80 / >90
Current:	600mA
LED source:	COB LED
Fixture material:	Aluminum
Finish:	White / Black



Measurement

Model	Dimension(mm)			Size(mm)
	A	B	C	
25W	85	211	57	Ø85*211

LM80

3 Yrs
Warranty

RCM

SAA

IP20

TUV

9/331 Ingles Street
Port Melbourne VIC 3207 Australia

info@greenlux.com.au
sales@greenlux.com.au

T 1300 650 625
www.greenlux.com.au