



Smart 01 Series LED Street Light

Available in Multiple Wattages
80% lumen maintenance at 50,000 hours

- 0% Mercury, 100% Environmentally friendly
- No IR or UV radiation, low heat generation
- 360° Rotatable
- Photocell or radar sensor available
- Suitable for 40-60mm diameter pole
- Self cleaning system, long lasting heat sink
- IP66 Rated
- 5 Year Warranty
- Applications include carparks, streets, tunnels, petrol stations, and stadiums

Specifications

Colour Range	3000-6500k
Power	30W ~ 170W
Lumen Efficiency	100-110lm/W
Input Voltage	100-277V
Chipset	CREE, Philips
Effective Illuminated Area	H6/6*8M H8/37*10M H10/45*12M
Driver	Meanwell, Philips & Class II
IK Rating	IK08
CRI	> 70
Power Factor	>0.95
Beam Angle	140°
Dimmable	1-10V Intelligent Dimming Interface (optional)



Dimensions & Materials

Product Dimensions (mm)	30-60W 522*245*132 70-170W 806*350*189
Materials	Die Cast Aluminium, Borosilicate Glass & Stainless Steel Fitting
Lens	UV Protection PC Lens
Housing Colour	Black / Silver





greenlux
cost reduction LED lighting

Smart 01 Series LED Street Light

Available in Multiple Wattages
80% lumen maintenance at 50,000 hours

PEDESTRIAN AREAS

Streets, paths and bike paths



STREETS

Residential streets



Shared zones, commercial streets in urban areas



ROADS

Rural roads



Urban roads



Motorways and ring roads




30-60W




70-170W




Distribution curve A (cd/klm)



Distribution curve B (cd/klm)




Distribution curve C (cd/klm)



Smart 01 Series LED Street Light

Available in Multiple Wattages
80% lumen maintenance at 50,000 hours

Model number & Dimensions



Model	Power	CCT	Voltage	Luminous Efficiency	Lumens	CRI	Lifespan
GMSMA-30W-01	30W	3000-5700K	AC 100-277V	95-105Lm/W	3040-3360Lm	70	50000 hrs
GMSMA-40W-01	40W	3000-5700K	AC 100-277V	95-105Lm/W	3895-4305Lm	70	50000 hrs
GMSMA-50W-01	50W	3000-5700K	AC 100-277V	95-105Lm/W	5130-5670Lm	70	50000 hrs
GMSMA-60W-01	60W	3000-5700K	AC 100-277V	95-105Lm/W	5890-6510Lm	70	50000 hrs
GMSMA-70W-01	70W	3000-5700K	AC 100-277V	95-105Lm/W	6840-7560Lm	70	50000 hrs
GMSMA-80W-01	80W	3000-5700K	AC 100-277V	95-105Lm/W	7600-8400Lm	70	50000 hrs
GMSMA-90W-01	90W	3000-5700K	AC 100-277V	95-105Lm/W	8550-9450Lm	70	50000 hrs
GMSMA-100W-01	100W	3000-5700K	AC 100-277V	95-105Lm/W	9500-10500Lm	70	50000 hrs
GMSMA-110W-01	110W	3000-5700K	AC 100-277V	95-105Lm/W	10450-11550Lm	70	50000 hrs
GMSMA-120W-01	120W	3000-5700K	AC 100-277V	95-105Lm/W	11400-12600Lm	70	50000 hrs
GMSMA-130W-01	130W	3000-5700K	AC 100-277V	95-105Lm/W	12255-13545Lm	70	50000 hrs
GMSMA-140W-01	140W	3000-5700K	AC 100-277V	95-105Lm/W	13205-14595Lm	70	50000 hrs
GMSMA-150W-01	150W	3000-5700K	AC 100-277V	95-105Lm/W	14060-15540Lm	70	50000 hrs
GMSMA-170W-01	170W	3000-5700K	AC 100-277V	95-105Lm/W	16150-17850Lm	70	50000 hrs