



greenlux
cost reduction LED lighting

Vestige Series 01 LED Track Light



- Eco-friendly. No UV or IR rays. No mercury or any other hazardous substances
- High quality COB light source
- Performs high efficiency and energy saving, Up to 80% energy saving compared to standard CFL
- Replaces traditional track lights
- IP20 for indoor use only
- 3 Years Warranty
- Applications include shopping centres, galleries, cafes, hotels, theatres, museums & display cases

Specifications

Colour Range 2700 ~ 5000K

Lumens 80 ~ 85lm/W

Input Voltage 100V/240V AC

	(L*W*H)	
Product Dimensions (mm)	12W	200*126*130
	25W	201*145*121
	35W	234*161*130
	45W	234*161*130
Housing Materials	PC Housing + Glass Diffuser	
Housing Colour	White or Black	
Beam angle	15° / 24° / 45° / 60°	
Power Factor	>0.9	
Dimmable	Triac Dimmer (option)	
CRI	>80	
Adapter	2/3/4 wires (option)	
Chipset	COB	






TRACK LIGHT

adopts COB LEDs with excellent color rendering index to increase the color fidelity of the target illuminated object



ANGLE



15°

24°



45°

60°

EXCELLENT HEAT DISSIPATION

even light output without glare & dark spot





Model	Voltage	Power	Non-DIM Lumen (±5%)			
			2700K	3000K	4000K	5000K
GUVES-12W-01	AC100-240V	12W	820	910	970	960
GUVES-25W-01	AC100-240V	25W	1870	1910	2160	2140
GUVES-35W-01	AC100-240V	35W	2430	2590	2950	2920
GUVES-45W-01	AC100-240V	45W	3130	3310	3590	3700

Model	Dimension (mm)			Product size (mm)	LED	Beam Angle	Dimmable (option)
	A	B	C				
GUVES-12W-01	126.5	104	194	126.5x104x194mm	COB	15° ~ 45°	Triac
GUVES-25W-01	141	121	201	141x121x201mm	COB	15° ~ 45°	Triac
GUVES-35W-01	161	131	234	161x131x234mm	COB	15° ~ 45°	Triac
GUVES-45W-01	161	131	234	161x131x234mm	COB	15° ~ 45°	Triac