

Opal Air-slots 3012 LED Panel

Model: GCOPA-42W-AS

Product Description

Housing: 0.6mm cold-roll steel housing under white powder coating with air slot

Diffuser: PMMA opal high optical grade diffuser providing good efficiency Uniform illuminating surface: no led "dots"

Mounting: recessed

Application: office, retail, healthcare, education, etc.



Specifications

Dimensions (LxWxH)	Model No.	GCOPA-42W-AS
	LxWxH (mm)	1195x295x65mm
	Power Consumption	42W
	Lumen Output (lm)	4352.3lm (at 4000K)
	Efficiency (lm/w)	103.60lm/W
LED Type	Beam Angle	101.3°
	LED Type	LED strip with Samsung 561B LED
	Information of Each Strip	22 LEDs, 300mA, 29.7-35.2V
	Colour Temp	3000K, 4000K, 5000K
	CRI	>80 / >90
Electrical Data	LED Driver	Philips Xitanium 57W 0.9/1.05A 54V 230V
	Input Voltage	220-240V
	Input Frequency (Hz)	50/60Hz
	Output Voltage	27-54V
	Output Current	1.05A
Packing (cm)	Power Factor	0.9719
	pcs/ctn	2pcs/ctn
	Outer Box	125x35x15 cm
Others	Certifications	CE(LVD+EMC), SAA, RoHS
	Warranty	5 Years
	Life Time	50,000 hours

Photometric & Diagram

