

Premium 905R LED Emergency Spitfire

Features

Standard Feature

- Comply to SAA/AS2293 Standard
- Recessed Installation
- Quick & Easy to Install and Maintain
- Low Power Consumption
- Low spaces illuminate, from 2 to 5m height
- Long lifespans
- Low Volt Cut-Off Preventing
- Battery Overdischarge Preventing
- Light warranty 5 Yrs / Battery 1 Yr

Electrical Feature

- Product Name: LED Emergency Spitfire
- Model No.: GSPRE-2W-905R / GSPRE-5W-905R
- LED Capacity: 2W / 5W
- Light Source: Cree LED
- Lumen Output: 146lm / 250lm
- Battery: Type - LiFePO4 / 2000mAh 3.7V
- Change-Over Time: <2Sec.
- Charging Time: <16Hr.
- Standby Time: >2Hr.
- Input Voltage: AC240V/50-60Hz
- Materials: Heat Sink - Aluminum / Surface Plate - Flame Retardant PC
- Installation: Recessed
- Cutout Hole: Φ 70mm
- Accessory: LED Lamp(with 140mm adapter plate) / Inverter / Battery Pack / 2m lead wire
- Operating Temperature: $-40^{\circ}\text{C} \sim +74^{\circ}\text{C}$
- IP Grade: IP30



Dimensions (unit: mm)



Recessed ceiling mounting

LED Lamp	Inverter	Battery Pack
Φ 143*28mm	111*42*25mm	80*35*23mm

