

Step D83 Series

WL3015 LED Wall Recessed Light



Specifications

| | |
|------------------------------|--|
| Light Source | Cree XPE-2 |
| System Wattage | 3W (700mA, 3V) |
| Lumen Flux | 180lm (3W, 3000K, Ra.80) |
| Colour Temperature | 2700K / 3000K / 4000K |
| CRI | Ra≥80, Ra≥90 |
| Chromaticity Rate | 3 MacAdam |
| Beam Angle | N/A |
| Service Lifetime | 50,000hrs, L70 |
| Ingress Protection | IP21 |
| Operation Voltage | 220-240Vac, 50/60Hz |
| Operation Temperature | -20~40D |
| Protection Class | I |
| Finishing | White RAL9016, Gloss 5 Black RAL9005, Gloss 5 |
| Bezel | White, black, silver grey, metallic grey |
| Construction | Aluminum |
| Mounting | Wall Recessed |
| Warranty | 5 years |
| Lighting Control | Non-dim / Triac dim |



Ordering Data

| WL3015 | Finish | Power | CCT | CRI | Beam |
|--------|--------|-------|-----|-----|------|
| Model | AW | 3 | 27 | R80 | N/A |
| | AB | | 30 | R90 | |
| | SG | | 40 | | |
| | MG | | | | |

Features

- 5 different bezels
- 3 different installations
- Triac dimmable driver
- Built-in driver

Accessories

- Bezel changeable, can be different colour
- PVC premount boxa

Diagram

